

# Product Data Sheet

## Drain Test Plug DTP



Reliable connections -  
worldwide!

### Product description:



Product Name	Drain Test Plug DTP
Product Group	Accessoires
Product Code	DTP
Sizes	DN 40 – 600
Rubber	EPDM
Plastic Type	–
Steel Quality	Aluminium
Pressure Rating	0.6 bar / 8.7 PSI
Standards	DIN EN 295-4, DIN EN 16397-2
Shore Resistance	n/a
Temperature Range	EPDM: -40 to 120 °C NBR: -30 to 100 °C
UV Resistance	EPDM: ✓, NBR: ✗
Oil / petrol Resistance	EPDM: ✗, NBR: ✓
Fire Performance	Class F
Soil Suitability	✓
Flush-mounted Suitability	✓
Tensile Strength	✗

Product Code		Size DN	Test thread (Inch)	Ø Minimum (mm)	Ø Maximum (mm)	Pressure (bar)	Net Weight (kg)
current	old						
DTP040	DTP40	40	1 ½	38	50	2.0	0.2
DTP050	DTP50	50	2	49	62	2.0	0.2
DTP065	DTP65	65	2 ½	62	77	2.0	0.3
DTP075	DTP75	75	3	73	89	1.3	0.3
DTP085	DTP85	85	3 ½	84	103	1.0	0.3
DTP100	DTP100/5	100	½	94	110	0.6	0.4
DTP115	DTP115	125 (PVCu)	½	108	120	0.6	0.5
DTP125	DTP125/5	125	½	121	138	0.6	0.8
DTP150	DTP150/5	150	½	146	163	0.6	0.7
DTP180	DTP180	200 (PVCu)	1	165	190	0.4	1.5
DTP200	DTP200	200	1	191	211	0.4	1.6
DTP225	DTP225	250 (PVCu)	1	216	235	0.4	1.9
DTP250	DTP250	250	1	244	260	0.4	2.4
DTP300	DTP300	300	1	296	314	0.4	3.4
DTP350	DTP350	350	1	340	375	0.3	5.5
DTP400	DTP400	400	1	390	425	0.3	6.5
DTP500	DTP500	500	2	495	525	0.3	14.0
DTP600	DTP600	600	2	590	630	0.2	16.5

Other sizes available on request.

**Note:** All information is based on the current state of our technical experience at the time of preparation. If necessary, they must be adapted to any changes. We reserve the right to make technical changes. Our general terms and conditions of sale and delivery apply.