

Product Data Sheet

Universal Saddle PA



Reliable connections -
worldwide!

Product description:



| | |
|---------------------------|--|
| Product Name | Saddle PA |
| Product Group | Lateral Connections |
| Product Code | PA |
| Sizes | lateral Pipe DN 100 – 160 |
| Rubber | EPDM |
| Steel Quality | 1.4301 / AISI 304 / V2A |
| Plastic Type | ABS |
| Pressure Rating | 0.5 bar / 7.3 PSI |
| Connecting to | smooth, thin-walled pipes, double-walled or ribbed pipes over DN 300 |
| Standards | EN 681-1 |
| Temperature Range | EPDM: -40 max. 120 °C ABS: -40 max. 85 °C |
| UV Resistance | ✓ |
| Oil / petrol Resistance | ✗ |
| Fire Performance | Class F |
| Soil Suitability | ✓ |
| Flush-mounted Suitability | ✓ |
| Tensile Strength | ✗ |
| Lateral Pipe Deflection | max. 8.5° |

| Product Code | | Inside Diameter Main Pipe (mm) | Wall thickness of the Main Pipe | Lateral Pipe | Core Drill (mm) | Net Weight (kg) |
|--------------|----------|--------------------------------|---------------------------------|-----------------------|-----------------|-----------------|
| current | old | | | | | |
| PA300-01 | PA1530 | 300 | various | DN 160 PVCu | 177 | 1.6 |
| PA400-01 | PA1540 | 400 | various | DN 160 PVCu | 177 | 1.7 |
| PA500-01 | PA1550 | 500 | various | DN 160 PVCu | 177 | 1.7 |
| PA600-01 | PA1560 | 600 | various | DN 160 PVCu | 177 | 1.7 |
| LPA110 | PA-AS110 | connecting kit | | DN 100 PVCu | | 1.0 |
| LPA130 | PA-AS130 | connecting kit | | DN 100 Vitrified Clay | | 1.1 |
| LPA180 | PA-AS180 | connecting kit | | DN 150 Vitrified Clay | | 1.2 |

Note: All information is based on the current state of our technical experience at the time of preparation. If necessary, they must be adapted to any changes. We reserve the right to make technical changes. Our general terms and conditions of sale and delivery apply.