

Product Data Sheet

Pipe Seal LSK



Reliable connections -
worldwide!

Product description:



Product Name	Pipe Seal LSK
Product Group	Pipe Seals
Product Code	LSK (was LSK960)
Sizes	40 – 500 mm
Rubber	EPDM / SBR / NBR
Pressure Rating	o. G.
Standards	EN 681-1
Shore Resistance	60
Temperature Range	EPDM: -40 to 120 °C SBR: -60 to 80 °C NBR: -30 to 100 °C
UV Resistance	EPDM: ✓ / NBR: ✗ / SBR: ✗
Oil / petrol Resistance	EPDM: ✗ / NBR: ✓ / SBR: ✗
Fire Performance	Class F
Soil Suitability	✓
Flush-mounted Suitability	✓
Tensile Strength	✗

Product Code	Size DN (mm)	OD (mm)	Core Drill (mm)	Insertion Depth (mm)	Net Weight (kg)
LSKM-40-75	40	40	75	50	0.3
LSKM-50-75	50	50	75	50	0.3
LSKM-63-89	60	63	89	50	0.3
LSKM-75-101	70	75	101	50	0.3
LSKM-90-116	90	90	116	50	0.3
LSKM-110-138	100	110	138	50	0.4
LSKM-110-138_N	100	110	138	50	0.4
LSKL-110-138-105	100	110	138	105	0.8
LSKM-125-151	125	125	151	50	0.4
LSKM-160-186	150	160	186	50	0.5
LSKM-160-186_N	150	160	186	50	0.5
LSKL-160-186-105	150	160	186	105	0.8
LSKM-170-196	150	170	196	50	0.5
LSKM-200-226	200	200	226	50	0.6
LSKM-220-222-246	200	222	246	50	0.8
LSKL-225-251	200	225	251	50	0.8
LSKM-250-276	250	250	276	50	0.7
LSKM-315-341	300	315	341	50	0.8
LSKM-400-426	400	400	426	50	1.0
LSKM-500-526	500	500	526	50	1.3

Overall length: 50 mm / *L - version: 105 mm

For customised products (as per delivery note), the required core bore is 26 mm larger than the outer diameter of the connecting pipe.

Note: All information is based on the current state of our technical experience at the time of preparation. If necessary, they must be adapted to any changes. We reserve the right to make technical changes. Our general terms and conditions of sale and delivery apply.