

Product Data Sheet

Universal Saddle PA



Reliable connections -
worldwide!

Product description:



Product Name	Saddle PA
Product Group	Lateral Connections
Product Code	PA
Sizes	lateral Pipe DN 100 – 160
Rubber	EPDM
Steel Quality	1.4301 / AISI 304 / V2A
Plastic Type	ABS
Pressure Rating	0.5 bar / 7.3 PSI
Connecting to	smooth, thin-walled pipes, double-walled or ribbed pipes over DN 300
Standards	EN 681-1
Temperature Range	-40 max. 85 °C
UV Resistance	✓
Oil / petrol Resistance	✗
Fire Performance	Class F
Soil Suitability	✓
Flush-mounted Suitability	✓
Tensile Strength	✗
Lateral Pipe Deflection	max. 8.5°

Product Code	Inside Diameter Main Pipe (mm)	Wall thickness Main Pipe	Lateral Pipe DN (mm)	Core Drill (mm)	Net Weight (kg)
PA300-01	300	various	160 PVCu	177	1.6
PA400-01	400	various	160 PVCu	177	1.7
PA500-01	500	various	160 PVCu	177	1.7
PA600-01	600	various	160 PVCu	177	1.7
LPA110	connecting kit		100 PVCu		1.0
LPA130	connecting kit		100 Vitrified Clay		1.1
LPA180	connecting kit		150 Vitrified Clay		1.2

Note: All information is based on the current state of our technical experience at the time of preparation. If necessary, they must be adapted to any changes. We reserve the right to make technical changes. Our general terms and conditions of sale and delivery apply.