

Product Data Sheet

Pipe Seal QS



Reliable connections -
worldwide!

Product description:



Product Name	Pipe Seal QS
Product Group	Pipe Seals
Product Code	QS
Sizes	110 – 200 mm
Rubber	SBR / NBR
Steel Quality	1.4301 / AISI 304 / V2A or 1.4404 / AISI 316 / V4A
Pressure Rating	o. G.
Standards	EN 681-1, EN 10088-2
Shore Resistance	60
Temperature Range	SBR: -60 to 80 °C NBR: -30 to 100 °C
UV Resistance	✗
Oil / petrol Resistance	SBR: ✗ / NBR: ✓
Fire Performance	Class F
Soil Suitability	✓
Flush-mounted Suitability	✓
Tensile Strength	✗

Product Code	Pipe OD (mm)	Core Drill (mm)	Overall Length (mm)	max. Wall Thickness (mm)	Net Weight (kg)
QS110-127-60	110	127	60	30	0.4
QS110-127-90	110	127	90	65	0.4
QS160-177-60	160	177	60	30	0.6
QS160-177-90	160	177	90	65	0.7
QS200-217-75	200	217	75	50	0.7
LPA110*	PA-adaptor for connecting DN 100 PVCu				1.0
LPA130*	PA-adaptor for connecting DN 100 vitrified clay				1.1
LPA180*	PA-adaptor for connecting DN 150 vitrified clay, twin-walled pipes				1.2
HS-K95-177	Hole saw for plastic pipes with chuck				-
STDN150	KG-socket (orange)				0.5
T-QS	Mouting Aid – Assembly tool				2.5

* More information in the product catalogue

Note: All information is based on the current state of our technical experience at the time of preparation. If necessary, they must be adapted to any changes. We reserve the right to make technical changes. Our general terms and conditions of sale and delivery apply.