Product Data Sheet
Bushes B

Reliable connections - worldwide!

Product description:

CE

Product Name	Bushes B
Product Group	Couplings
Product Code	B
Sizes	from 11 mm
Rubber	EPDM / NBR
Pressure Rating	analogue to the Coupling used
Shear load resistance	✗
Standards	EN 295-4, EN 681-1
Shore Resistance	60
Deflection	analogue to the Coupling used
Temperature Range	EPDM: -40 to 120 °C NBR: -30 to 100 °C
UV Resistance	EPDM: ✓ / NBR: ✗
Oil / petrol Resistance	EPDM: ✗ / NBR: ✓
Fire Performance	Class F
Soil Suitability	✓
Flush-mounted Suitability	✓
Tensile Strength	✗

All compensating rings are available in:

- Production range YY = 4 mm
- Production range YY = 8 mm
- Production range YY = 12 mm*
- Production range YY = 16 mm
- Production range YY = 24 mm*
- Production range YY = 32 mm*

We configure our Fernco compensating rings as required. The pipe outside diameter must be specified when ordering.

*Production is only possible from an outside diameter of 200/250 mm.

Various thicknesses are also available in **NBR quality (oil and petrol resistant)** – plus 25 % of the list price.

Note: All information is based on the current state of our technical experience at the time of preparation. If necessary, they must be adapted to any changes. We reserve the right to make technical changes. Our general terms and conditions of sale and delivery apply.