


Product Data Sheet

Drain Test Plug DTP



Reliable connections -
worldwide!

Product description:



Product Name	Drain Test Plug DTP
Product Group	Accessories
Product Code	DTP
Sizes	DN 40 – 600
Rubber	EPDM / NBR
Plastic Type	–
Steel Quality	Aluminium
Pressure Rating	see table below
Standards	DIN EN 295-4
Shore Resistance	–
Temperature Range	EPDM: -40 to 120 °C NBR: -30 to 100 °C
UV Resistance	EPDM: ✓ / NBR: ✗
Oil / petrol Resistance	EPDM: ✗ / NBR: ✓
Fire Performance	Class F
Soil Suitability	✓
Flush-mounted Suitability	✓
Tensile Strength	✗

Product Code	Size DN (mm)	Test thread (inch)	Ø Minimum (mm)	Ø Maximum (mm)	Pressure (bar)	Net Weight (kg)
DTP040	40	½	38	50	2.0	0.2
DTP050	50	½	49	62	2.0	0.2
DTP065	65	½	62	77	2.0	0.3
DTP075	75	½	73	89	1.3	0.3
DTP085	85	½	84	103	1.0	0.3
DTP100	100	½	94	110	0.6	0.4
DTP115	125 (PVCu)	½	108	120	0.6	0.5
DTP125	125	½	121	138	0.6	0.8
DTP150	150	½	146	163	0.6	0.7
DTP180	200 (PVCu)	1	165	190	0.4	1.5
DTP200	200	1	191	211	0.4	1.6
DTP225	250 (PVCu)	1	216	235	0.4	1.9
DTP250	250	1	244	260	0.4	2.4
DTP300	300	1	296	314	0.4	3.4
DTP350	350	1	340	375	0.3	5.5
DTP400	400	1	390	425	0.3	6.5
DTP500	500	2	495	525	0.3	14.0
DTP600	600	2	590	630	0.2	16.5

Note: All information is based on the current state of our technical experience at the time of preparation. If necessary, they must be adapted to any changes. We reserve the right to make technical changes. Our general terms and conditions of sale and delivery apply.