

Product Data Sheet

Saddle TA



Reliable connections -
worldwide!

Product description:



Product Name	Saddle TA
Product Group	Lateral Conections
Product Code	TA
Sizes	lateral Pipe DN 100 – 200
Rubber	PVC, Neopren
Steel Quality	1.4301 / AISI 304 / V2A
Plastic Type	PVC
Pressure Rating	0.6 bar / 8.7 PSI
Connecting to	All smooth-walled pipes DN 160 – 600
Standards	EN 10088-2
Temperature Range	0 to 45 °C
UV Resistance	✓
Oil / petrol Resistance	✗
Fire Performance	Class F
Soil Suitability	✓
Flush-mounted Suitability	✓
Tensile Strength	✗
Lateral Pipe Deflection	max. 5°

Product Code	Lateral Pipe	Main Pipe OD (mm)	Core Drill (mm)	Pressure (bar)	Net Weight (kg)
TA11090	PVCu / Cast Iron DN 100	160 – 400	127	0.6	3.0
TA11045	PVCu / Cast Iron DN 100	160 – 400	oval	0.6	3.2
TA16090	PVCu / Cast Iron DN 150	200 – 400	172	0.6	4.8
TA16045	PVCu / Cast Iron DN 150	200 – 400	oval	0.6	5.2
TA20045	PVCu DN 200	300 – 600	oval	0.6	8.6

Note: All information is based on the current state of our technical experience at the time of preparation. If necessary, they must be adapted to any changes. We reserve the right to make technical changes. Our general terms and conditions of sale and delivery apply.