

Product Data Sheet

Compact Seal Cavo-In CSSCI



Reliable connections -
worldwide!

Product description:



Product Name	Compact Seal Cavo-In CSSCI
Product Group	Pipe lead-trough
Product Code	CSSCI
Sizes	OD 63 – 160
Rubber	EPDM / PUR
Steel Quality	1.4301 / AISI 304 / V2A
Pressure Rating	1.5 bar / 21.8 PSI
Vacuum	–
Standards	Sound insulation according to DIN 4109
Shore Resistance	EPDM: 55 / PUR: 25
Temperature Range	-40 to 120 °C
Radon proof	✓
UV Resistance	✓
Oil / petrol Resistance	EPDM: ✗, PUR: ✓
Fire Performance	Class F
Soil Suitability	✓
Flush-mounted Suitability	✓
Tensile Strength	✗

Also available with KTW (drinking water) approval.

Product Code	KWR/KSR Pipe-OD (mm)	ID (mm)	Segment set of cuts (mm)	Cable Ø (mm)
CSSCI063-618	63	53	10 / 14 / 18	6 – 18
CSSCI075-624	75	64	10 / 14 / 18 / 24	6 – 24
CSSCI110-636	110	93	10 / 14 / 18 / 24 / 30 / 36 / 42 / 48	6 – 48
CSSCI110-648	110	93	1x 10 / 14 / 18 1x 10 / 14 / 18 / 24 / 30 / 36	1x 6 – 18 1x 6 – 36
CSSCI110-4618	110	93	4x 10 / 14 / 18	4x 6 – 48
CSSCI160-3642	160	138	3x 10 / 14 / 18 / 24 / 30 / 36 / 42	3x 6 – 42
CSSCI160-4636	160	138	4x 10 / 14 / 18 / 24 / 30 / 36	4x 6 – 36
CSSCI160-6630	160	138	6x 10 / 14 / 18 / 24 / 30	6x 6 – 30

Note: All information is based on the current state of our technical experience at the time of preparation. If necessary, they must be adapted to any changes. We reserve the right to make technical changes. Our general terms and conditions of sale and delivery apply.