


Product description:



Product Name	Adaptor Coupling AC / AR
Product Group	Couplings
Product Code	AC / AR / PAC
Sizes	24 – 235 mm
Rubber	EPDM / NBR
Steel Quality	1.4301 / AISI 304 / V2A or 1.4404 / AISI 316 / V4A
Plastic Type	–
Pressure Rating	0.6 bar / 8.7 PSI
Vacuum	-0.3 bar
Jetting Resistance	up to 180 bar / 2610 psi
Standards	DIN EN 295-4, DIN EN 681-1, ETA 12-0410
Shore Resistance	60
Temperature Range	EPDM: -40 to 120 °C NBR: -30 to 100 °C
UV Resistance	EPDM: ✓ / NBR: ✗
Oil / petrol Resistance	EPDM: ✗ / NBR: ✓
Fire Performance	Class F
Soil Suitability	✓
Flush-mounted Suitability	✓
Tensile Strength	–

Product Code	OD-Range 1 (mm)	OD-Range 2 (mm)	Width – B (mm)	Ext. Dim. – A (mm)	Torque (Nm)	Pressure (bar)	Net Weight (kg)
AR1500	170 – 191	160 – 170	100	215	6	0.6	0.7
AR2250	260 – 285	240 – 250	130	310	13	0.6	1.8
AR3000	360 – 385	325 – 335	160	415	13	0.6	2.8

Note: All information is based on the current state of our technical experience at the time of preparation. If necessary, they must be adapted to any changes. We reserve the right to make technical changes. Our general terms and conditions of sale and delivery apply.

Adaptor Coupling AC / AR / PAC

Product Code	OD-Range 1 (mm)	OD-Range 2 (mm)	Width – B (mm)	Ext. Dim. – A (mm)	Torque (Nm)	Pressure (bar)	Net Weight (kg)
PAC0301	30 – 34	24 – 28	80	60	6	0.6	0.1
PAC0431	38 – 43	30 – 35	80	70	6	0.6	0.2
PAC0562	48 – 56	38 – 43	80	80	6	0.6	0.2
PAC0682	60 – 68	38 – 43	80	95	6	0.6	0.2
PAC0923	82 – 92	48 – 56	80	120	6	0.6	0.3
PAC0924	82 – 92	60 – 68	80	120	6	0.6	0.3
AC0633	53 – 63	40 – 50	90	90	6	0.6	0.2
AC0894	75 – 89	53 – 63	90	115	6	0.6	0.3
AC1155	100 – 115	75 – 90	90	140	6	0.6	0.4
AC1201	105 – 120	35 – 45	100	145	6	0.6	0.4
AC1221	110 – 122	80 – 95	100	150	6	0.6	0.5
AC1225	110 – 122	48 – 56	100	150	6	0.6	0.4
AC1226	110 – 122	60 – 68	100	150	6	0.6	0.4
AC5144	110 – 125	100 – 115	100	150	6	0.6	0.6
AC1361	121 – 136	80 – 95	100	160	6	0.6	0.5
AC1362	121 – 136	100 – 115	100	160	6	0.6	0.5
AC4000	121 – 136	110 – 121	100	160	6	0.6	0.5
AC1452	130 – 145	110 – 125	120	170	6	0.6	0.6
AC1552	140 – 155	90 – 105	120	180	6	0.6	0.6
AC1602	144 – 160	110 – 122	120	185	6	0.6	0.7
AC1603	144 – 160	121 – 136	120	185	6	0.6	0.8
AC1702	155 – 170	110 – 125	120	195	6	0.6	0.8
AC1703	155 – 170	130 – 145	120	195	6	0.6	0.8
AC1922	170 – 192	110 – 122	120	220	6	0.6	0.9
AC1923	170 – 192	121 – 136	120	220	6	0.6	0.9
AC1924	170 – 192	144 – 160	120	220	6	0.6	0.9
AC2000	180 – 200	130 – 145	150	225	6	0.6	1.2
AC2001	180 – 200	155 – 170	150	225	6	0.6	1.2
AC6000	180 – 200	160 – 180	150	225	6	0.6	1.1
AC2100	185 – 210	100 – 115	150	235	6	0.6	1.2
AC2101	185 – 210	160 – 180	150	235	6	0.6	1.2
ACOS2152*	195 – 215	100 – 115	150	240	6	0.6	1.4

*exzentrische Ausführung.

Continued on the next page.

Note: All information is based on the current state of our technical experience at the time of preparation. If necessary, they must be adapted to any changes. We reserve the right to make technical changes. Our general terms and conditions of sale and delivery apply.

Adaptor Coupling AC / AR / PAC

Product Code	OD-Range 1 (mm)	OD-Range 2 (mm)	Width – B (mm)	Ext. Dim. – A (mm)	Torque (Nm)	Pressure (bar)	Net Weight (kg)
AC2154	190 – 215	150 – 165	150	240	6	0.6	1.2
AC2254	200 – 225	160 – 175	150	250	6	0.6	1.3
AC2352	210 – 235	110 – 122	150	260	6	0.6	1.4
AC2353	210 – 235	121 – 136	150	260	6	0.6	1.4
AC2354	210 – 235	144 – 160	150	260	6	0.6	1.4
AC2355	210 – 235	170 – 192	150	260	6	0.6	1.4
AC2356	210 – 235	190 – 215	150	260	6	0.6	1.5
AC2654	240 – 265	144 – 160	150	290	6	0.6	1.7
AC2655	240 – 265	170 – 192	150	290	6	0.6	1.7
AC2656	240 – 265	190 – 215	150	290	6	0.6	1.7
AC2657	240 – 265	210 – 235	150	290	6	0.6	2.0
AC2754	250 – 275	160 – 175	150	300	6	0.6	2.0
AC2756	250 – 275	200 – 225	150	300	6	0.6	2.0
AC9001	260 – 285	180 – 205	150	310	13	0.6	2.3
AC2904	265 – 290	144 – 160	150	315	13	0.6	2.0
AC2907	265 – 290	210 – 235	150	315	13	0.6	2.0
AC2908	265 – 290	235 – 260	150	315	13	0.6	2.0
ACOS2956*	270 – 295	185 – 210	150	320	13	0.6	2.5
AC3204	295 – 320	144 – 160	150	345	13	0.6	3.0
AC3205	295 – 320	170 – 192	150	345	13	0.6	3.0
AC3207	295 – 320	210 – 235	150	345	13	0.6	2.5
AC3208	295 – 320	240 – 265	150	345	13	0.6	2.5
AC3209	295 – 320	265 – 290	150	345	13	0.6	2.5
ACOS3351*	310 – 335	180 – 205	150	360	13	0.6	2.6
AC3608	335 – 360	240 – 265	165	390	13	0.6	3.5
AC3609	335 – 360	265 – 290	165	390	13	0.6	3.5
AC3600	335 – 360	295 – 320	165	390	13	0.6	3.0
AC3858	360 – 385	240 – 265	165	415	13	0.6	3.5
AC3850	360 – 385	300 – 325	165	415	13	0.6	3.0
AC4208	395 – 420	240 – 265	165	450	13	0.6	4.0
AC4209	395 – 420	265 – 290	165	450	13	0.6	4.0

*exzentrische Ausführung.

Note: All information is based on the current state of our technical experience at the time of preparation. If necessary, they must be adapted to any changes. We reserve the right to make technical changes. Our general terms and conditions of sale and delivery apply.