


Product Data Sheet

Drainage Coupling DC / PC



Reliable connections -
worldwide!

Product description:



Product Name	Drainage Coupling DC / PC
Product Group	Couplings
Product Code	DC / PC
Sizes	30 – 275 mm (PC 35 – 100, DC 95 – 275)
Rubber	EPDM / NBR
Plastic Type	–
Steel Quality	1.4301 / AISI 304 / V2A or 1.4404 / AISI 316 / V4A
Pressure Rating	0.6 bar / 8.7 PSI
Vacuum	-0.3 bar
Jetting Resistance	up to 180 bar / 2610 psi
Standards	DIN EN 295-4
Shore Resistance	60
Temperature Range	EPDM: -40 to 120 °C NBR: -30 to 100 °C
UV Resistance	EPDM: ✓ / NBR: ✗
Oil / petrol Resistance	EPDM: ✗ / NBR: ✓
Fire Performance	Class F
Soil Suitability	✓
Flush-mounted Suitability	✓
Tensile Strength	–

Note: All information is based on the current state of our technical experience at the time of preparation. If necessary, they must be adapted to any changes. We reserve the right to make technical changes. Our general terms and conditions of sale and delivery apply.

Product Code	Range (mm)	Width – B (mm)	Ext. Dim. – A (mm)	Torque (Nm)	Pressure (bar)	Net Weight (kg)
PC035	30 – 35	70	60	6	0.6	0.2
PC043	38 – 43	70	70	6	0.6	0.2
DC050	40 – 50	90	75	6	0.6	0.2
PC056	48 – 56	70	80	6	0.6	0.2
DC065	50 – 65	90	90	6	0.6	0.3
PC068	60 – 68	80	95	6	0.6	0.2
DC075	70 – 76	110	100	6	0.6	0.3
PC076	68 – 76	80	95	6	0.6	0.3
PC085	76 – 85	80	100	6	0.6	0.3
PC092	85 – 92	80	110	6	0.6	0.3
DC095	80 – 95	100	120	6	0.6	0.4
PC100	92 – 100	80	125	6	0.6	0.3
DC115	100 – 115	100	140	6	0.6	0.5
DC125	110 – 125	100	150	6	0.6	0.7
DC135	120 – 135	120	165	6	0.6	0.7
DC150	135 – 150	120	180	6	0.6	0.7
DC165	150 – 165	120	195	6	0.6	0.8
DC175	160 – 175	120	205	6	0.6	0.8
DC185	170 – 185	120	215	6	0.6	0.8
DC195	180 – 195	120	225	6	0.6	0.8
DC215	200 – 215	150	245	6	0.6	1.2
DC225	210 – 225	150	255	6	0.6	1.2
DC250	235 – 250	150	280	6	0.6	1.2
DC265	250 – 265	150	295	13	0.6	1.3
DC275	260 – 275	150	305	13	0.6	1.5

Note: All information is based on the current state of our technical experience at the time of preparation. If necessary, they must be adapted to any changes. We reserve the right to make technical changes. Our general terms and conditions of sale and delivery apply.