

Product Data Sheet

Saddle FA-B



Reliable connections -
worldwide!

Product description:



Product Name	Saddle FA-B
Product Group	Lateral Connections
Product Code	FAXXXB
Sizes	lateral Pipe DN 150 / 200
Rubber	EPDM
Steel Quality	1.4301 / AISI 304 / V2A
Plastic Type	ABS
Pressure Rating	0.5 bar / 7.3 PSI
Connecting to	Concrete pipes and -shafts DN 150: from DN 300 DN 200: from DN 400
Jetting Resistance	up to 180 bar / 2610 psi
Standards	EN 681-1, EN 10088-2
Temperature Range	-40 to 85 °C
UV Resistance	✓
Oil / petrol Resistance	✗
Fire Performance	Class F
Soil Suitability	✓
Flush-mounted Suitability	✓
Tensile Strength	✗
Lateral Pipe Deflection	max. 5.7°

Product Code	Size DN (mm)	Core Drill (mm)	main pipe from DN (mm)	Net Weight (kg)
FA150BS	150 Clay	172 +1/-0	300	2.5
FA150BS-MB	150 PVCu	172 +1/-0	300	3.0
FA150BS-MB	150 Cast Iron	172 +1/-0	300	3.0
FA150BS-MB	150 Ductile Iron	172 +1/-0	300	3.0
FA150BS-MB	150 GRP	172 +1/-0	300	3.0
FA150BS-MB	150 UR II	172 +1/-0	300	3.0
FA200B	200 Clay	232 +1/-0	400	3.5
FA200B-MB	200 PVCu	232 +1/-0	400	4.8
FA200B-MB	200 Cast Iron	232 +1/-0	400	4.8
FA200B-MB	200 Ductile Iron	232 +1/-0	400	4.8
FA200B-MB	200 GRP	232 +1/-0	400	4.8
FA200B-MB	200 UR II	232 +1/-0	400	4.8
ESH150B	Attention: different discounts			0.6
ESH200B	Attention: different discounts			0.9

Note: All information is based on the current state of our technical experience at the time of preparation. If necessary, they must be adapted to any changes. We reserve the right to make technical changes. Our general terms and conditions of sale and delivery apply.