

Product Data Sheet

Saddle FA-KG



Reliable connections -
worldwide!

Product description:



Product Name	Saddle FA-KG
Product Group	Lateral Connections
Product Code	FAXXXKG
Sizes	lateral Pipe DN 150 / 200
Rubber	EPDM
Steel Quality	–
Plastic Type	PP
Pressure Rating	0.6 bar / 8.7 PSI
Connecting to	Concrete pipes / Shafts from DN 300
Jetting Resistance	up to 180 bar / 2610 psi
Standards	EN 681-1 / DiBt
Temperature Range	0 to 80 °C
UV Resistance	✓
Oil / petrol Resistance	✗
Fire Performance	Class F
Soil Suitability	✓
Flush-mounted Suitability	✓
Tensile Strength	✗
Lateral Pipe Deflection	–

Product Code	Lateral Pipe	main pipe OD (mm)	Core Drill (mm)	Pressure (bar)	Net Weight (kg)
FA150KG	PVCu / Cast Iron DN 150	300	186 ± 1.8	0.6	1.3
FA200KG	PVCu DN 200	400	226 ± 2	0.6	2.0

Note: All information is based on the current state of our technical experience at the time of preparation. If necessary, they must be adapted to any changes. We reserve the right to make technical changes. Our general terms and conditions of sale and delivery apply.