

Product Data Sheet

Saddle FA-ST



Reliable connections -
worldwide!

Product description:



Product Name	Saddle FA-ST
Product Group	Lateral Connections
Product Code	FA150ST
Sizes	lateral Pipe DN 150
Rubber	EPDM
Steel Quality	1.4301 / AISI 304 / V2A
Plastic Type	ABS
Pressure Rating	1 bar / 14.5 PSI
Connecting to	Vitrified Clay Pipes DN 250N – 350H / DN 200VT – 300 VT
Jetting Resistance	up to 180 bar / 2610 psi
Standards	EN 681-1, EN 10088-2
Temperature Range	EPDM: -40 to 120 °C ABS: -40 to 85 °C
UV Resistance	✓
Oil / petrol Resistance	✗
Fire Performance	Class F
Soil Suitability	✓
Flush-mounted Suitability	✓
Tensile Strength	✗
Lateral Pipe Deflection	5°

Product Code	Size DN (mm)	Core Drill (mm)	Net Weight (kg)
FA150ST	150 Clay	172 +1/-0	0.9
FA150ST-KG	150 PVCu / PP	172 +1/-0	1.4
LPA110*	100 PVCu / PVC	-	1.0
LPA130*	100 Clay	-	1.1
LPA180*	150 Clay	-	1.2

Note: All information is based on the current state of our technical experience at the time of preparation. If necessary, they must be adapted to any changes. We reserve the right to make technical changes. Our general terms and conditions of sale and delivery apply.