

Product Data Sheet

Saddle FA-UNI



Reliable connections -
worldwide!

Product description:



Product Name	Saddle FA-UNI
Product Group	Lateral Connections
Product Code	FA150U
Sizes	lateral Pipe DN 150
Rubber	EPDM
Steel Quality	1.4301 / AISI 304 / V2A
Plastic Type	ABS
Pressure Rating	1 bar / 14,5 PSI
Connecting to	Universal, over DN 250
Jetting Resistance	up to 180 bar / 2610 psi
Standards	EN 681-1, EN 10088-2
Temperature Range	EPDM: -40 to 120 °C ABS: -40 to 85 °C
UV Resistance	✓
Oil / petrol Resistance	✗
Fire Performance	Class F
Soil Suitability	✓
Flush-mounted Suitability	✓
Tensile Strength	✗
Lateral Pipe Deflection	max. 7°

Product Code	lateral Pipe DN (mm)	Core Drill (mm)	Net Weight (kg)
FA150U	150 Clay	172 +1/-0	1.5
FA150U-MB	150 PVCu	172 +1/-0	2.1
FA150U-MB	150 Cast Iron	172 +1/-0	2.1
FA150U-MB	150 Ductile Iron	172 +1/-0	2.1
FA150U-MB	150 GRP	172 +1/-0	2.1
FA150U-MB	150 UR II	172 +1/-0	2.1

Note: All information is based on the current state of our technical experience at the time of preparation. If necessary, they must be adapted to any changes. We reserve the right to make technical changes. Our general terms and conditions of sale and delivery apply.