

# Product Data Sheet

## Saddle Storm-T



Reliable connections -  
worldwide!

### Product description:



Product Name	Saddle Storm-T
Product Group	Lateral Connections
Product Code	ST
Sizes	lateral Pipe DN 150
Rubber	EPDM
Steel Quality	-
Plastic Type	ABS
Pressure Rating	0.5 bar / 7.3 PSI
Connecting to	all plastic pipes DN 250 – 600
Vacuum	-0.3 bar
Jetting Resistance	up to 180 bar / 2610 psi
Standards	EN 681-1
Shore Resistance	60
Temperature Range	-40 to 85 °C
UV Resistance	✓
Oil / petrol Resistance	✗
Fire Performance	Class F
Soil Suitability	✓
Flush-mounted Suitability	✓
Tensile Strength	✗
Lateral Pipe Deflection	max. 4.5°

Product Code	DN Main Pipe (mm)	Wall Thickness Range (mm)	max. OD Main Pipe (mm)	Inside Diameter ID (mm)	DN Lateral Pipe (mm)	Drilled Hole Size (mm)	Net Weight (kg)
ST150-300	250 – 300	5 – 30.5	355	147.5 – 153	150 / 160	177 +1/-0.5	1.2
ST150-375-450	375 – 450	5 – 45	540	147.5 – 153	150 / 160	177 +1/-0.5	1.2
ST150-500-600	500 – 600	10 – 60	720	147.5 – 153	150 / 160	177 +1/-0.5	1.2

**Note:** All information is based on the current state of our technical experience at the time of preparation. If necessary, they must be adapted to any changes. We reserve the right to make technical changes. Our general terms and conditions of sale and delivery apply.